



MLT-2™

**INSTALLER
SERIES**

COMPLETE 5.1 CHANNEL HOME THEATER SYSTEM

	MLT-2 SPEAKER	MLT-2 CENTER
Frequency Response	110–20,000 Hz ±2db	130–20,000 Hz ±2db
Sensitivity	88 dB@2.83 volts/meter	89 dB@2.83 volts/meter
Impedance	Compatible with 4, 6, or 8 Ohm rated amps	Compatible with 4, 6, or 8 Ohm rated amps
Crossover Freq.	2000 Hz	2300 Hz
Tweeter Type	1" soft dome	1" soft dome
Woofer Type	4.5" poly cone	2 x 3.5" poly cone
Enclosure Type	Sealed	Sealed
Recommended Amp	15–100 watts	15–100 watts
Size (h x w x d)	7.75" x 4.625" x 5.75"	4.25" x 12" x 5.5"

	MLT-2 SUBWOOFER
Frequency Response	37–200 Hz ± 3 dB. Anechoic in the LFE mode.
Low Pass Filter	50Hz–200 Hz
Phase	0°, 180°
Woofer Type	10" high-excursion, paper cone
Enclosure Type	Bass reflex
Amplifier	120 watts RMS (360 watts peak)
Inputs	Left & Right/LFE RCA Line Level
Size (h x w x d)	16" x 11.5" x 15.5"



MARTIN LOGAN®

The Great American Speaker Company
www.martinlogan.com

For detailed amplifier recommendations and complete specifications visit www.MartinLogan.com.

Application:

Complete home theater 5.1 channel (fronts, center, surrounds, and sub) solution for small rooms.

The MLT-2 5.1-channel home theater package features a compact design and superb sound quality. The front, center, and surround satellites include 1-inch titanium dome tweeters and 4.5-inch or 3.5-inch poly cone woofers. The powered subwoofer, featuring a 10" driver, plays down to 37 Hz with a 360 watts dynamic peak amplifier (120 watts RMS).

Key Features:

- 4 x front/surround speakers
- 1 x center channel speaker
- 1 x subwoofer (LFE)
- Quick, no-hassle installation
- Wall mount option
- Bookshelf mount option
- 1-inch soft dome tweeters
- Low-distortion 4.5-inch and 3.5-inch poly cone woofers
- 10-inch paper cone subwoofer

FINISH

Black



MLT-2 front/surround