

Dynamo[™] 1000

STEREO/HOME THEATER SUBWOOFER

THE MOST POWERFUL DYNAMO SUB... IDEAL FOR LARGER ROOMS!

True high-end performance. Home-friendly aesthetics. And power, lots of power! In a nutshell, that's the incredible Dynamo 1000 subwoofer. Dramatic bass detail and attack, superb extension and room-shaking output ensure a music and home theater experience like no other subwoofer in its class can deliver. Features include a 500-watt RMS, 1,000-watt peak amplifier and 12-inch cone driver. Its standard down-firing configuration quickly converts into a front-firing configuration, ideal for discrete installations. The finishing touch—a wireless receiver for a 'cablefree' environment (with the addition of a SWT-1 wireless transmitter, sold separately).

Frequency Response Low Pass Filter Frequencies Low Frequency Driver Amplifier Inputs Wireless Receiver Wireless Transmitter Weight Down-Firing Orientation Dimensions (HxWxD) Front-Firing Orientation Dimensions (HxWxD)

22–200 Hz ± 3dB 35–120 Hz 12" (30.5 cm) poly cone; sealed 500 watts rms (1000 watts peak) Left & Right/LFE RCA Built-in SWT-1 Wireless Transmitter, sold separately 34 lbs. (15.4 kg) 14.6" x 13.7" x 14.6" (36.9 x 34.8 x 37 cm) 15.5" x 13.7" x 14.4" (39.3 x 24.8 x 36.5 cm)



The Great American Speaker Company www.martinlogan.com For detailed amplifier recommendations and complete specifications visit www.MartinLogan.com.

Application:

Home theater and stereo subwoofer ideal for large and medium rooms.

Capable of both front- and downfiring operation, Dynamo 1000 provides superb bass from any location—whether in a corner, behind furniture, or installed in a cabinet.

Key Features:

- Wireless-ready, just add the SWT-1 wireless transmitter
- Front- or down-firing configuration
- Inverse mathematical equalization
 for linear output
- Internally braced composite cabinet
- Sealed enclosure for woofer control
- Ultra efficient true 500-watt amplifier
- Low-distortion 12-inch cone woofer
- Custom ETC[™] spikes

FINISH OPTIONS

Black

WOOFER





No tools are required to convert from a front to a down firing configuration.



Optional SWT-1 subwoofer wireless transmitter.