

# Motion SLM

## SPECIFICATIONS

**Frequency Response**  
110–25,000 Hz ± 3 dB

**Dispersion**  
80° x 80°

**High Frequency Driver**  
1" x 1.4" (2.6cm x 3.6cm) Folded Motion Transducer with 5.25" x 1.75" (13.3cm x 4.4cm) diaphragm.

**Low Frequency Transducer**  
Two 4" (10.2cm) paper cone. Two 4" (10.2cm) paper cone passive radiators.

**Sensitivity**  
90 dB @ 2.83 volts/ meter

**Impedance**  
4 Ohms. Compatible with 4, 6 or 8 Ohm rated amplifiers.

**Recommended Amplifier Power**  
20–140 watts


**Crossover Frequency**  
2,600 Hz

**Components**  
Custom air core coil and low DCR steel laminate inductors. Polyester film capacitors in series and low DF electrolytic capacitors in parallel. Overall system thermal/current protection.

**Weight**  
6.5 lbs. (3.0 kg)

**Dimensions**  
25.3" x 6.4" x 1.83"  
(64.2cm x 16.2cm x 4.75cm)

*Specifications are subject to change without notice.*



The slender Motion SLM speakers features an advanced resolution Folded Motion™ tweeter, two 4-inch high-excursion fiber cone woofers and two passive bass radiators for maximum controlled low-end bass extension - all in an ultra-slim profile designed expressly for super-thin TVs.



### Slender Profile & Stunning Performance

The secret to the Motion SLM's outstanding performance is the innovative dual 4-inch, ultra-slim fiber cone woofers and dual 4-inch high-velocity passive bass radiators, paired with a Folded Motion tweeter to create stunning acoustical alchemy typically found in much larger speaker systems. Hidden discretely underneath the grille, the drivers are held securely in place by a solid, black-anodized brushed aluminum baffle. The high-gloss black Motion SLM cabinet is only 1.45-inches thin, for a total wall protrusion of 1.83-inches with magnetic grille and included wall mount bracket.

### The Perfect LCR System

The Folded Motion tweeter has an 80° x 80° dispersion pattern, which allows the Motion SLM to sound exactly the same in a horizontal or vertical orientation, making them perfect for Left-Center-Right (LCR) system applications. The logo on the grille is magnetic and can move and rotate to the proper aesthetically pleasing location in any orientation. Each speaker includes a curved black-glass base allowing the Motion SLM to sit on a shelf or equipment cabinet. Also included are "kick-stand" brackets that attach to the back of the cabinet, allowing them to free-stand for center channel applications.