

A MASTERPIECE OF DESIGN & ENGINEERING. Distilling nearly forty years of innovative audio design and engineering into a startlingly fresh loudspeaker ideal.

MartinLogan unveils the Classic ESL 9, its newest modern Masterpiece. All the familiar elements of MartinLogan's flagship ESL series are here, with some revolutionary refinements. The heart of this exceptional loudspeaker is its 9.2-inch-wide XStat™ Curvilinear Line Source (CLS™) vacuum-bonded electrostatic transducer. Advanced MicroPerf stator technology reveals more of the diaphragm surface area than any other electrostatic panel in this size class, efficiently increasing the narrow panel's output. Ultra-rigid AirFrame Blade construction reduces performance-robbing vibrations, its shape creating an expressive alignment with the woofer cabinet. Deep bass is rendered with unflinching accuracy and authority by dual 8-inch low-distortion, high-excursion aluminum cone woofers in a beautifully sculpted enclosure.

QUICK SPECS:

- 44" x 9.2" XStat™ CLS™ Transducer
- · Dual 8-inch Aluminum Cone Woofers
- 34–23,000 Hz ±3dB Frequency Response
- Custom 5-Way Bi-Wire Binding Posts













Finish Options:



System Frequency Response

 $34-23,000 \text{ Hz} \pm 3 \text{db}$

Recommended Amplifier Power

50–400 watts per channel at 4 Ohms

Dispersion

Horizontal: 30 degrees

Vertical: 44-inch (112 cm) line source

Sensitivity

 $90 \, \mathrm{dB} \, / \, 2.83 \, \mathrm{volts} \, / \, \mathrm{meter}$

Impedance

Nominal: 4 ohms, 0.8 ohms @ 20 kHz

Crossover Frequency

380 Hz

High/Mid Frequency Driver

XStat CLS Electrostatic transducer

Panel dimensions: 44×9.2 inch $(112 \times 23.4 \text{ cm})$

Radiating area: 405 in² (2,621 cm²)

Woofers

 $2x\ 8''\ (20.3cm)$ cast basket, high excursion, rigid aluminum cone with extended throw drive assembly, non-resonance asymmetrical chamber format.

Components

Custom-wound audio transformer, air core coils, low DCR steel laminate coils, polyester capacitors

Signal Inputs

Custom 5-way bi-wire tool-less binding posts

Power Draw

Max: 2W per channel Standby: <1W per channel

Weight

78 lbs. each (35.4 kg)

Size $(H \times W \times D)$

 $59.8 \times 10.4 \times 25.4$ -inch (152 x 26.4 x 64.6 cm)

Specifications are subject to change without notice.