



MLT-1™

COMPLETE 5.1 CHANNEL HOME THEATER SYSTEM

**INSTALLER
SERIES**

	MLT-1 SPEAKER	MLT-1 CENTER
Frequency Response	125–20,000 Hz ± 2 db	130–20,000 Hz ± 2 db
Sensitivity	87 dB@2.83 volts/meter	89 dB@2.83 volts/meter
Impedance	Compatible with 4, 6, or 8 Ohm rated amps	Compatible with 4, 6, or 8 Ohm rated amps
Crossover Freq.	2000 Hz	2200 Hz
Tweeter Type	1" soft dome	1" soft dome
Woofer Type	3.5" poly cone	2 x 3.5" poly cone
Enclosure Type	Sealed	Sealed
Recommended Amp	15–80 watts	15–100 watts
Size (h x w x d)	7" x 4.25" x 5.5"	4.5" x 12" x 5.63"

	MLT-1 SUBWOOFER
Frequency Response	40–200 Hz ± 3 dB. Anechoic in the LFE mode.
Low Pass Filter	50Hz–200 Hz
Phase	0°, 180°
Woofer Type	8" high-excursion, paper cone
Enclosure Type	Bass reflex
Amplifier	100 watts RMS (250 watts peak)
Inputs	Left & Right/LFE RCA Line Level
Size (h x w x d)	14" x 11" x 12.5"



MARTIN LOGAN®

The Great American Speaker Company
www.martinlogan.com

For detailed amplifier recommendations and complete specifications visit www.MartinLogan.com.

Application:

Complete home theater 5.1 channel (fronts, center, surrounds, and sub) solution for small rooms.

The MLT-1 5.1 home theater package features compact design and superb sound quality. The front, center, and surround satellites feature 1-inch titanium dome tweeters and 3.5-inch poly cone woofers. The powered subwoofer, featuring a 8" driver, plays down to 40 Hz with a 250 watts dynamic peak amplifier (100 watts RMS).

Key Features:

- 4 x front/surround speakers
- 1 x center channel speaker
- 1 x subwoofer (LFE)
- Quick, no-hassle installation
- Wall mount option
- Bookshelf mount option
- 1-inch soft dome tweeters
- Low-distortion 3.5-inch poly cone woofers
- 8-inch paper cone subwoofer

FINISH

Black



MLT-1 front/surround

©2010 MartinLogan, Ltd. All rights reserved.