

Grotto™i

STEREO/HOME THEATER SUBWOOFER

COMPACT AND ACCURATE

A powerful 300 watt (900 watt peak) low-distortion, high-reliability amplifier delivers extremely articulate bass without the need for transient-blurring ported or passive radiator enclosures common to many modern subwoofers. A proprietary servo system further ensures that output from Grotto i's 10-inch high-resolution aluminum cone woofer is dramatically free of distortion and provides tight, well defined bass in any system.

Frequency Response	22–120 Hz ± 3dB
Low Pass Filter Frequencies	30, 35, 45, 55, 65, and 80 Hz
High Pass Filter Frequency	70 Hz
25Hz Level Control	±10dB
Low Frequency Driver	10″ (25.4 cm) aluminum cone
Amplifier	300 watts (900 watts peak)
Inputs	Left/Right RCA Line Level, RCA LFE, Speaker Level
Outputs	RCA Sub Out, RCA Right/Left
Weight	51 lbs. (23.2 kg)
Dimensions (HxWxD)	18.6" x 15.2" x 13.8" (47.3 x 38.6 x 35 cm)

MARTIN LOGAN® The Great American Speaker Company www.martinlogan.com

For detailed amplifier recommendations and complete specifications visit www.MartinLogan.com.

Application:

Home theater and stereo subwoofer ideal for medium and small rooms.

The world's most affordable, compact, and versatile servo-control equipped subwoofer, Grotto i, delivers extremely articulate bass without the need for exaggerated amplifier power ratings.

Key Features:

- Advanced Servo Control
- Ultra efficient 300-watt amplifier
- Low-distortion 10-inch aluminum cone woofer
- 25Hz level control
- Precision low-pass crossover filters
- Unique crossover and level settings for simultaneous 2-channel and LFE connections
- Custom ETC[™] spikes

FINISH OPTIONS



WOOFER

Visit configurator.martinlogan.com to explore the full range of finish options.

