Motion 60XT

SPECIFICATIONS

Frequency Response

35-25,000 Hz ± 3 dB

Dispersion

High Frequency Driver

1.25" x 2.4" (3.2cm x 6.1cm) Folded Motion XT Transducer with 4.5" x 2.75" (11 4cm x 7cm) diaphraam

Mid Frequency Transducer

6-1/2" (16.5cm) aluminum cone with cast polymer basket. Sealed chamber format. Rigid structured dust cap to reduce cone break-up modes.

Low Frequency Transducer

Two 8" (20.3cm) aluminum cone with cast aluminum basket. Non-resonant asymmetrical chamber format. Rigid structured dust cap to reduce cone break-up modes.

Sensitivity

94 dB @ 2.83 volts/meter

Impedance

4 Ohms. Compatible with 4, 6, or 8 Ohm rated amplifiers.

Recommended Amplifier Power

20 - 400 watts

Crossover Frequency

400 & 2,200 Hz

Cabinet

Components

Custom air core coil and low DCR steel laminate inductors. Polypropylene film capacitors in series and low DF electrolytic capacitors in parallel. Tweeter thermal/current protection.

Custom 5-way bi-wire tool-less binding posts

Weight 66 lbs. (30 kg)

Dimensions

48" x 11.4" x 14.4" (121.8cm x 29cm x 36.6cm)

Specifications are subject to change without notice.











The dominant Motion 60XT speaker features our largest and most accurate Folded Motion™ XT tweeter, a 6-1/2" aluminum cone midrange and two 8" high-performance aluminum cone bass woofers.





Audiophile Dominance with Style

XT stands for extreme, and for good reason. Motion 60XT speakers play louder, lower, and with unflinching accuracy. Dual 8" woofers and rear-firing bass ports create astonishing deep, precise bass, while a dedicated mid woofer promotes an open, revealing and authentic midrange. Paring this powerful trio with our most accurate Folded Motion XT tweeter creates audible acoustic alchemy that delivers an engaging and encompassing experience, cutting straight to the emotion locked inside your favorite recordings.

