

State-of-the-art **Truth in Sound**—from extreme home theater to transcendent two-channel listening, the Masterpiece™ CI Series offers the biggest, boldest, and most lifelike performance possible. A tribute to the acoustic achievements of MartinLogan's original iconic masterpiece, our electrostatic speakers.

Statement™

40XW



- 40x drivers
- **16x tweeters:** Folded Motion® XT Obsidian
 - **16x mid:** 3.5-inch • **8x bass:** 6.5-inch
- Unidirectional carbon fiber multi-section cones with a Nomex® backer
- Line source configuration with controlled dispersion sound radiation
 - Vojtko™ crossover network constructed from audiophile-grade components
- Phenolic baffle • Sealed back box • Surface mount grille

SPECIFICATIONS

Frequency Response	48–25,000 Hz ± 3 dB
Tweeter Dispersion (horizontal x vertical)	80° x 52-inch line source
Sensitivity	95 dB @ 2.83 volts/ meter
Impedance	4 ohms. Compatible with 4, 6, or 8 ohm rated amps.
Crossover Frequency	300, 2700 Hz
High-Frequency Drivers	Sixteen 1.25 x 2.4 inch (3.2 x 6.1 cm) Folded Motion XT Obsidian transducer with 4.5 x 2.75 inch (11.4 x 7 cm) diaphragm.
Mid-Frequency Drivers	Sixteen 3.5-inch (8.9 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Low-Frequency Drivers	Eight 6.5-inch (16.5 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Binding Post Inputs	Push style (two sets for easy installation)
Components	Custom air core coil inductors, polypropylene film capacitors, and low DF electrolytic capacitors.
Suitable Amplifier Range	50–800 watts
Max Power Handling	400 watts
Weight	150 lb (68.1 kg)
Required Wall Cavity (width)	Minimum: 14.5 inch (368 mm) Maximum: 16.5 inch (420 mm)
Required Wall Cavity (height, unobstructed)	Minimum: 89 inch (2260 mm)
Required Wall Cavity (depth)	Minimum: 3.5 inch (89 mm)
Enclosure (width x height x depth, excludes padding)	14.3 x 84.2 x 3.4 inch (361 x 2137 x 86 mm)
Grille (height x width)	11.5 x 59.5 inch (292 x 1511 mm)
Installation Kit (included)	Choose appropriate size 1/2-inch drywall (PN: 40XWIWK05) 5/8-inch drywall (PN: 40XWIWK0625)



State-of-the-art **Truth in Sound**—from extreme home theater to transcendent two-channel listening, the Masterpiece™ CI Series offers the biggest, boldest, and most lifelike performance possible. A tribute to the acoustic achievements of MartinLogan's original iconic masterpiece, our electrostatic speakers.

Monument™

7XW



7x drivers

- **1x tweeter:** Folded Motion® XT Obsidian
 - **1x mid:** 6.5-inch
 - **2x bass:** 6.5-inch
 - **3x passive:** 6.5-inch
- Unidirectional carbon fiber multi-section cones with a Nomex® backer
- Vojtko™ crossover network constructed from audiophile-grade components
 - Phenolic baffle
 - Sealed back box
- Die-cast aluminum mounting-lock system
 - Pre-install brackets (sold separately)

SPECIFICATIONS

Frequency Response	52–25,000 Hz ± 3 dB
Tweeter Dispersion (horizontal x vertical)	80° x 30°
Sensitivity	95 dB @ 2.83 volts/ meter
Impedance	4 ohms. Compatible with 4, 6, or 8 ohm rated amps.
Crossover Frequency	200, 3200 Hz
Tweeter Aiming	Rotatable tweeter for horizontal or vertical installations
High-Frequency Driver	1.25 x 2.4 inch (3.2 x 6.1 cm) Folded Motion XT Obsidian transducer with 4.5 x 2.75 inch (11.4 x 7 cm) diaphragm.
Mid-Frequency Driver	6.5-inch (16.5 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Low-Frequency Drivers	Two 6.5-inch (16.5 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Passive Radiators	Three 6.5-inch (16.5 cm) unidirectional black carbon fiber cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Binding Post Inputs	Push style (two sets for easy installation)
Components	Custom air core coil inductors, polypropylene film capacitors, and low DF electrolytic capacitors. Thermal/current protection.
Suitable Amplifier Range	20–300 watts
Max Power Handling	150 watts
Weight	44.5 lb (20.2 kg)
Overall Size (height x width x depth)	46.86 x 10.6 x 4.11 inch (1190.2 x 269.2 x 104.3 mm)
Required Opening (including tolerance)	45.57 x 9.29 inch (1157 x 236 mm)
Projection From the Wall Surface	0.31 inch (7.8 mm)
Depth Required Behind the Wall Surface	3.8 inch (96.5 mm)
Optional Accessories	Pre-install bracket (PN: 7XWBRK)



State-of-the-art **Truth in Sound**—from extreme home theater to transcendent two-channel listening, the Masterpiece™ CI Series offers the biggest, boldest, and most lifelike performance possible. A tribute to the acoustic achievements of MartinLogan's original iconic masterpiece, our electrostatic speakers.

Tribute™ 5XW



- **5x drivers**
- **1x tweeter:** Folded Motion® XT Obsidian
 - **2x mid/bass:** 5.25-inch
 - **2x passive:** 6.5-inch
- Unidirectional carbon fiber multi-section cones with a Nomex® backer
- Vojtko™ crossover network constructed from audiophile-grade components
 - Phenolic baffle
 - Sealed back box
- Die-cast aluminum mounting-lock system
 - Pre-install brackets (sold separately)

SPECIFICATIONS

Frequency Response	71–25,000 Hz ± 3 dB
Tweeter Dispersion (horizontal x vertical)	80° x 30°
Sensitivity	94 dB @ 2.83 volts/ meter
Impedance	4 ohms. Compatible with 4, 6, or 8 ohm rated amps.
Crossover Frequency	2250 Hz
Tweeter Aiming	Rotatable tweeter for horizontal or vertical installations
High-Frequency Driver	1.25 x 2.4 inch (3.2 x 6.1 cm) Folded Motion XT Obsidian transducer with 4.5 x 2.75 inch (11.4 x 7 cm) diaphragm.
Low-Frequency Drivers	Two 5.25-inch (13.33 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Passive Radiators	Two 6.5-inch (16.5 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Binding Post Inputs	Push style (two sets for easy installation)
Components	Custom air core coil inductors, polypropylene film capacitors, and low DF electrolytic capacitors. Thermal/current protection.
Suitable Amplifier Range	20–250 watts
Max Power Handling	125 watts
Weight	25.5 lb (11.6 kg)
Overall Size (height x width x depth)	31.13 x 10.6 x 4.09 inch (790.82 x 269.2 x 103.93 mm)
Required Opening (including tolerance)	29.82 x 9.29 inch (757 x 236 mm)
Projection From the Wall Surface	0.31 inch (7.8 mm)
Depth Required Behind the Wall Surface	3.8 inch (96.5 mm)
Optional Accessories	Pre-install bracket (PN: 5XWBRK)



State-of-the-art **Truth in Sound**—from extreme home theater to transcendent two-channel listening, the Masterpiece™ CI Series offers the biggest, boldest, and most lifelike performance possible. A tribute to the acoustic achievements of MartinLogan's original iconic masterpiece, our electrostatic speakers.

Icon™ 3XW



- **3x drivers**
- **1x tweeter:** Folded Motion® XT Obsidian
 - **2x mid/bass:** 5.5-inch
- Unidirectional carbon fiber multi-section cones with a Nomex® backer
- Vojtko™ crossover network constructed from audiophile-grade components
 - Phenolic baffle
 - Sealed back box
- Die-cast aluminum mounting-lock system
 - Pre-install brackets (sold separately)

SPECIFICATIONS

Frequency Response	78–25,000 Hz ± 3 dB
Tweeter Dispersion (horizontal x vertical)	80° x 30°
Sensitivity	94 dB @ 2.83 volts/ meter
Impedance	4 ohms. Compatible with 4, 6, or 8 ohm rated amps.
Crossover Frequency	2400 Hz
Tweeter Aiming	Rotatable tweeter for horizontal or vertical installations
High-Frequency Driver	1.25 x 2.4 inch (3.2 x 6.1 cm) Folded Motion XT Obsidian transducer with 4.5 x 2.75 inch (11.4 x 7 cm) diaphragm.
Low-Frequency Drivers	Two 5.25-inch (13.33 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Binding Post Inputs	Push style
Components	Custom air core coil inductors, polypropylene film capacitors, and low DF electrolytic capacitors. Thermal/current protection.
Suitable Amplifier Range	20–250 watts
Max Power Handling	125 watts
Weight	15.5 lb (7 kg)
Overall Size (height x width x depth)	15.98 x 9.94 x 4.11 inch (405.95 x 252.6 x 104.3 mm)
Required Opening (including tolerance)	14.66 x 8.64 inch (372 x 219 mm)
Projection From the Wall Surface	0.31 inch (7.8 mm)
Depth Required Behind the Wall Surface	3.8 inch (96.5 mm)
Optional Accessories	Pre-install bracket (PN: 3XWBRK)



State-of-the-art **Truth in Sound**—from extreme home theater to transcendent two-channel listening, the Masterpiece™ CI Series offers the biggest, boldest, and most lifelike performance possible. A tribute to the acoustic achievements of MartinLogan's original iconic masterpiece, our electrostatic speakers.

Sistine™ 4XC



- **4x drivers**
- **1x tweeter:** Folded Motion® XT Obsidian
 - **2x mid:** 3.5-inch
 - **1x bass:** 8-inch
- Unidirectional carbon fiber multi-section cones with a Nomex® backer
- Vojtko™ crossover network constructed from audiophile-grade components
 - Sealed back box
- Die-cast aluminum mounting-lock system
 - Pre-install brackets (sold separately)
 - Square grille (sold separately)

SPECIFICATIONS

Frequency Response	63–25,000 Hz ± 3 dB
Tweeter Dispersion (horizontal x vertical)	30° x 80°
Sensitivity	92 dB @ 2.83 volts/ meter
Impedance	4 ohms. Compatible with 4, 6, or 8 ohm rated amps.
Crossover Frequency	400, 2250 Hz
High-Frequency Driver	1.25 x 2.4 inch (3.2 x 6.1 cm) Folded Motion XT Obsidian transducer with 4.5 x 2.75 inch (11.4 x 7 cm) diaphragm.
Mid-Frequency Drivers	Two 3.5-inch (8.9 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Low-Frequency Driver	8-inch (20.3 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Controls	<i>Tweeter Level (dB):</i> +2, -2, 0 <i>Position:</i> Front R/Rear L, Front L/Rear R, For center choose either
Binding Post Inputs	Push style
Components	Custom air core coil inductors, polypropylene film capacitors, and low DF electrolytic capacitors. Thermal/current protection.
Suitable Amplifier Range	20–300 watts
Max Power Handling	150 watts
Weight	13.5 lb (6.1 kg)
Overall Size (diameter x depth)	12.8 x 7.5 inch (325 x 190 mm)
Required Opening (including tolerance)	11.46 inch (291 mm)
Projection From the Wall Surface	0.26 inch (6.6 mm)
Depth Required Behind the Wall Surface	7.2 inch (184 mm)
Optional Accessories	Pre-install bracket (PN: C8HTBRK) Square grille (PN: C8HTSQ)

